

5 which the prompt and reliable identification of the failure should be obtained, cause

by the technicians comprises a diagnosis device developed to simulate the loads of each appliance model and which should be carried by the technician in charge, who will couple it to the command module of the appliance. The diagnosis device is then operated by the technician, according to a predetermined sequence of procedures to be followed, in such a way as to simulate the operational conditions of the involved loads and to check the conditions of the means that form the command module.

etc.) of the command module, verifying whether a failure occurred in one of the components and the real need for replacing it.

Nevertheless, this type of diagnosis system requires a skilled and careful operator to provide a reliable diagnosis, in order to avoid an undesirably high rate of diagnosis errors.

25 operational conditions of the command module, requiring other test procedures to check the
operational conditions of the different loads of the electric circuit of the appliance.

5 There are also known sophisticated solutions of self-diagnosis, which precisely indicate the defective component, such as those provided in some appliances, equipments, and devices. However, these solutions of directly detecting the voltage values are relatively expensive, increasing the final cost of the appliance.

10 By reason of the deficiencies known heretofore, as discussed above, it is the generic object of the present invention to provide a diagnosis system to be incorporated into an electric household appliance, such as a refrigerator, freezer, or air conditioner, in order to allow for a prompt, simple, and reliable identification of the operational failures, not only in the command module, but also in the loads energized thereby, without requiring the technician in charge to
15 carry a special device to be coupled to the command module, or to base his conclusion on the interpretation of different test parameters to be observed and considered.

20 Summary of the Invention

25 coupled thereto.

{W:\04304\0202992us0\00922477.DOC 100%}

5 second voltage and to process these values, indicating in an interface the existence of failure in at least one of the elements defined by the command module, by the switches and their respective electronic controls, in case any second voltage presents a value which is equal or to higher than that of the first voltage. In this case, the control unit can, optionally, interrupt the sequence of tests.

10 Brief Description of the Drawings

The invention will be described now, with reference to the enclosed drawings directed to a possible way of carrying out the invention, and in which:

15 unit;

Figure 2 is a simplified scheme of the voltmeter operatively associated with the control unit and with the loads of the refrigeration appliance;

Figure 3 is a block diagram of the operational sequence defined by the control unit, for obtaining and processing the voltage values during the execution of the diagnosis;

20 Figure 4 is a block diagram of the operational sequence defined by the control unit in the step of acquiring the voltage values;

Figure 5 is a block diagram similar to that of figure 4, but illustrating a possible variation for the operational sequence in the step of acquiring the voltage values;

25 of checking the operational conditions of the command module;

Figure 7 is a block diagram similar to that of figure 6, but illustrating a possible variation for the operational sequence in the step of checking the conditions of the command module; and

Figures 8 and 9 are block diagrams of two possible processing operational sequences of the control unit in the step of checking the operational conditions of the loads of the refrigeration appliance to be submitted to a diagnosis.

Detailed Description of the Invention

As illustrated in the drawings and as mentioned above, the present diagnosis system is applied to electric household appliances, such as freezers, etc., presenting different loads 10, which can take the form of, for example, a compressor, lamps, a defrost electric resistance, etc., and whose activation, energized by an AC power system, is effected by respective switches 20 operated by respective electronic controls 30 operatively associated thereto, as a function of the operational requirements of the refrigeration appliance.

The electronic controls are disposed in parallel and generally DC energized by a power source 40 connected to the AC power system.

The electronic controls 30 are operatively coupled and generally physically mounted to a command module 50, which is energized by the power source 40 and constructed so as to command the activation of the different loads 10 by energizing the electronic controls 30 of the respective switches 20. The command module 50 can present any known construction usually utilized to command the automatic activation of the different loads 10 of an appliance, as a function of the operational parameters selected by the user and defined during project.

In the illustrated embodiment described below, the loads 10 are defined by the compressor, by the defrost resistance and by the internal light (lamp) of the cabinet of a refrigeration appliance. The fans, if present in the refrigeration appliances of the forced ventilation (no frost) type can have their operational conditions also diagnosed by the same procedures considered herein, and the fans can be operationally included in the definition of the loads whose correct operation is desired to be checked through the present diagnosis system.

5 according to a predetermined operational sequence of tests, as described ahead.

the different operational conditions of the switches 20.

10 As illustrated in figure 2, the voltmeter 60 comprises a signal conditioning circuit 61, connected to the inlet of each load 10 upstream the respective switch 20 and supplying voltage signals from the inlet of the load 10 to an AD converter 62 connected to the control unit 70.

The signal conditioning circuit 61 is formed, in the illustrated example, by a resistive divider with “n” inlets corresponding to the quantity of loads to be diagnosed (in the present case, for example, three inlets), by a signal rectifying diode and a signal filtering capacitor, in order to adjust the inlet AC voltage to the levels required by the AD converter 62.

The signal conditioning circuit further comprises an assembly of resistors 63 respectively connected in parallel with the loads 70 for providing the adequate maintenance of a predetermined voltage in the circuit supplying the loads 10 upon opening thereof.

20 The voltage signals obtained from the inlet of the loads 10 are conditioned by the conditioning circuit and sent to the AD converter 62 and thence to the control unit 70.

The electronic control unit 10 and the command module 50 are operatively associated with an interface 80 that can take different forms, such as a connector for the acquisition or transfer of signals, a visual or sonorous alarm, or a display also mounted to the structure of the cabinet of the refrigeration appliance in a visible place and which can be further provided with activating

5

0

5

20

- opening all the switches 20;

- awaiting a certain minimum time to elapse, for example about 5 seconds, and measuring and recording a first voltage V_{off} corresponding to the voltage value in the inlet of all the loads 10, with the switches 20 opened;
- closing the switch 20 of the defrost resistance;
- 5 - awaiting the certain minimum time to elapse and measuring and recording the voltage value V_{res} in the inlet of the defrost resistance;
- opening the switch 20 of the defrost resistance;
- closing the switch 20 of the lamp;
- awaiting the certain minimum time to elapse and measuring and recording the voltage value
- 10 V_{lamp} in the inlet of the lamp, whose switch 20 is closed;
- opening the switch 20 of the lamp;
- closing the switch 20 of the compressor;
- awaiting the certain minimum time to elapse and measuring and recording a second voltage value V_{comp} in the inlet of the compressor, whose switch 20 is closed; and
- 15 - maintaining the switch of the compressor closed.

In case one desires to obtain voltage values in the inlet of each two or three loads 10 together, with their respective switches 20 being simultaneously closed, it is only necessary, before opening a switch 20 after acquiring the second voltage V_{res} , V_{lamp} , V_{comp} of the respective load 10, to close another switch 20 and to measure and record the voltage value in the inlet of

20 the two or three loads 10, whose switches are found simultaneously closed. It should be noted that the loads 10 to be associated for the joint measure of the voltage are those which can be simultaneously energized in the household electric appliance.

In the exemplary operational sequence of tests illustrated in figure 5, the acquisition of the voltage values follows the steps below:

- Once the voltage values in the inlet of the loads 10 have been recorded in the conditions in which the respective switches 20 are opened, closed, and optionally closed in different groups, the control unit 70 initiates a second processing phase, diagrammatically illustrated in figure 6

According to figure 6, the phase of checking the plate of the command module 50 comprises

the steps of comparing, sequentially, the first voltage V_{off} in the inlet of each of the loads 10 presenting the respective switches 20 in the open condition with the second voltages V_{res} , V_{lamp} , V_{comp} in the inlet of the loads 10 presenting the respective switches 20 in the closed condition, and indicating, in the interface 80, whether the first voltage V_{off} is higher than the second voltage V_{res} , V_{lamp} , V_{comp} in the inlet of the respective load 10 with the switch closed. In case this condition occurs in all the loads 10, the processing system concludes that all respective switches 20 and the electronic controls 30 of the command module 50 are in good conditions, since no failures have been detected in the switches 20 or in their associated electronic controls 30.

In case in any of the steps of comparing the first Voff voltage with the second voltages Vres, Vlamp, Vcomp of the loads 10 a different condition is detected in the relation of expected values, i.e., any second voltage with a value equal to or higher than that of the first voltage, the control unit 70 indicates the anomaly at the interface 80, informing the existence of a failure in one of the components of the plate of the command module 50, leading to the replacement of the component. In this case, the diagnosis procedure is ended, since it is not safe to continue the tests of the loads 10 with the deficient command module 50. In the hypothesis the first voltage Voff is lower than the second voltages Vres, Vlamp, Vcomp, the control unit 70 will produce in the interface 80 the indications that the problem is neither located in the command module 50 nor in its components defined by the switches 20 and respective electronic controls 30.

In figure 7 of the enclosed drawings, there is illustrated another construction for the operational sequence of checking the command module 50. In this construction, the checking of the plate of the command module 50 comprises a first step of defining a limit voltage V_{lim}

lower than the first voltage V_{off} as a safety value. In a possible way of carrying out the invention, the limit value V_{lim} is approximately equal to 87.5% of the value of V_{off} .

Once the limit voltage value V_{lim} has been defined, the checking comprises the steps of comparing, sequentially, the second voltages V_{res} , V_{lamp} , V_{comp} in the inlet of the loads 10 having the respective switches 20 in the closed condition with the limit voltage V_{lim} , and indicating in the interface 80 whether any of the second voltages V_{res} , V_{lamp} , V_{comp} is greater than the limit voltage V_{lim} .

In case this condition occurs in any of the loads 10, the processing system concludes that there is a failure in a component of the command module 50 operatively related to the load 10 and whose second voltage is greater than the limit voltage V_{lim} . In this case, the diagnosis procedure is not interrupted yet, differing from the procedure described in relation to the operational sequence illustrated in figure 6.

In the hypothesis of any second voltage V_{res} , V_{lamp} , V_{comp} being lower than or equal to the limit voltage V_{lim} , the control unit 70 may produce in the interface 80 the indications that the problem might not be located in the command module 50 and in its components defined by the switches 20 and respective electronic controls.

In the example of figure 7, there is provided an additional sequence for checking the command module 50, as illustrated in the lower half of the figure. According to the operational sequence, a first processing step is provided, in which there is defined a first processing voltage V_{proc1} lower than the second voltage of a first load 10, which in the present example is represented by the second voltage V_{lamp} in the inlet of the lamp. In a way of carrying out the invention, the first processing voltage V_{proc1} corresponds to about 87.5% of the value of the second voltage V_{lamp} in the inlet of the first load, i.e., of the lamp. Subsequently, the following steps are processed by the control unit 70:

- checking whether the second voltage V_{comp} of a second load 10, for example the compressor, is lower than the first voltage V_{off} , whether the switch 20 of the first load 10 defined by the lamp is operative, and whether the second voltage V_{lamp} , V_{comp} in the inlet of

- indicating, in the interface 80, by means of the control unit 70, whether the three conditions above have been fulfilled or not fulfilled, the last hypothesis leading to the indication that a problem exists in the switch 20 of the second load 10 represented by the compressor;

- indicating in the interface 80, by means of the control unit 70, whether the three conditions above have been fulfilled or not fulfilled, the last hypothesis leading to the indication that a problem exists in the switch 20 of the third load 10, represented by the defrost resistance;

- checking whether the second voltage V_{lamp} of the first load 10 represented by the lamp is lower than the first voltage V_{off} , whether the switch 20 of the second load 10 represented by the compressor is operative, and whether the second voltage V_{lamp_Vcomp} in the inlet of the second and of the first load 10, respectively represented by the compressor and the lamp, is lower than the second processing voltage V_{proc2} ;

This alternative processing illustrated in figure 7 allows checking more safely the operation of the command module 50, even considering substantial variations in the voltage supplied by the power system.

5 step of comparing the second voltages V_{res} , V_{lamp} , V_{comp} related to the loads 10 with the switches 20 in the closed condition.

control unit 70 verifies whether the first voltage V_{off} (switches opened) is higher than a certain reference voltage value V_{ref} , which in the example is 1.3V. In case this occurs, all the loads are considered to be in a good state, since the reference voltage V_{ref} illustrates a voltage value above which the first voltage V_{off} is compulsorily located with a certain margin of safety, in case the loads 10 are in adequate operational conditions.

15 Thus, in case a first voltage V_{off} (switches opened) is detected to be higher than the reference voltage V_{ref} , it can be concluded that all the loads are really correctly closed, i.e., in adequate operational conditions.

10 are open. It should be noted herein that the present diagnosis system does not detect short circuits in the loads 10.

25 presenting a defect.

This second operational sequence of load tests comprises several steps, each basically comparing the second voltage V_{res} , V_{lamp} , V_{comp} of each load 10 (switch 20 closed) with a

Thus, in case any second voltage V_{res} , V_{lamp} , V_{comp} measured in the inlet of a load 10

presents a value that is equal to or lower than that minimum value V_{min} , the control unit will send to the interface 80 an instruction identifying the open condition (failure) of the load. In case a step of checking the operational condition of a load 10 concludes for the acceptance of the load, the control unit 70 will pass to the next step of checking the condition of another load, with no need of indicating in the interface 80 whether this or that load is in acceptable conditions.

Upon completion of the steps of checking the condition of each of the loads 10, the control unit 70 instructs the command module 50 to normally operate the refrigeration appliance.

To carry out a new diagnosis procedure, the technician in charge may press a key in the appliance or disconnect the latter from the power system, awaiting a certain time until the compressor is activated, and then he reconnects the appliance and introduces in the command module 50, in the predetermined time, the specific password to initiate the diagnosis phases by instruction of the control unit 70.